| ANCHOR BLOCKS | | CALCULATIONS, CONTRACTOR'S | |
|---------------------------------------|---------|--------------------------------------|---|
| Design Criteria | 4-32 | Purpose of 2- | 4 |
| APPROVAL OF FALSEWORK DRAWINGS | | CAMBER | |
| By Registered Engineer | 2-5 | Defined 3-1: | 3 |
| General discussion | 2-1 | General Discussion 3-13, 3-14 | 4 |
| Railroad Approval required | 2-5 | Stress on camber strips 3-14 | |
| Responsibility for | 1-5 | | • |
| neepenenamy re- | . • | CATALOG, DATA | |
| ASSUMED HORIZONTAL LOAD | | For cables 4-26 | 5 |
| General discussion | 3-2 | For shoring systems 6-1 | 1 |
| See also Horizontal Design Load | | For manufactured assemblies 4-32 | 2 |
| | | Furnished when requested 2-2 | 2 |
| BEAM CONTINUITY | | | |
| As a design consideration | 3-15 | CHRONOLOGICAL LOG | |
| Effect on falsework towers | 6-9 | Preparation of 2-6 | 6 |
| BEAM DEFLECTION | | COEFFICIENT OF FRICTION | |
| See Def lection | | For anchor block design 4-32 | , |
| 000 201 10011011 | | For falsework design 3-17 | |
| BEAM HANGERS | | | |
| Limitations on use | 4-34 | CLEARANCE ZONE | |
| | | At traffic openings 8-1 | J |
| BEAM SPAN | | | |
| In timber members | 4-2 | COLLAPSE | |
| | | As a failure mode 5-1 | i |
| BEAMS | | | |
| See Steel Beams | | COLLAPSING FORCE | _ |
| See Timber Beams | | Defined 5-5 | 5 |
| BENDING STRESS | | COLUMNS | |
| In steel beams | 4-20 | See Steel Posts and Columns | |
| In timber beams | 4-3 | See Timber Posts | |
| | | Pile Column 7-35,7-36 | ; |
| BI-AXIAL BENDING | | | |
| As a design consideration | 4-21 | COMBINED STRESSES | |
| | | As a design consideration 5-2,5-14 | Ļ |
| BOLTED CONNECTIONS | | in pile bents 7-34,38,39,47,48,49,52 | 2 |
| At traffic openings | 8 4 | | |
| Design criteria | 4-9 | CONCRETE ANCHOR BLOCKS | |
| | | Design criteria 4-32 | 2 |
| BRACING | | | |
| See Cable Bracing | | CONSTRUCTION JOINTS | _ |
| See Diagonal Bracing | | Falsework bent required 3-16 | Š |
| See External Bracing | | | |
| See Falsework Bracing System | | CONSTRUCTION SEQUENCE | _ |
| See Temporary Bracing at F/W Openings | 3 | As a design consideration 3-16 | j |
| CABLE BRACING | | CONTINUITY | |
| Anchor blocks, Design of | 4-32 | See Beam Continuity | |
| Cable connectors | 4-29 | • | |
| Catalog data required | 4-26 | CONTINUOUS PADS AND STILLS | |
| Design load | 4-28 | Criteria for analysis 7-3 | 3 |
| Inspection of | 9-7 | Effective length formula 7-4,7-5,7-8 | 3 |
| Safety factor | 4-29 | | |
| When used as bracing to | | CONTRACTUAL RELATIONSHIPS | |
| prevent internal collapse | 4-26 | General discussion I- | 5 |
| When used as temporary' bracing 4-2 | 25,9-13 | | |
| | | | |

| 0000510 | | DOUBLE CARO | |
|-------------------------------------|--------------|--|--------------------|
| CORBELS Multiple corbel systems | 7-11 | DOUBLE CAPS | 0.0 |
| Load distribution | 7-11 7-20 | At traffic openings Stability of | 8-3 5-73 |
| Timber corbels | 7-20 7-21 | Stability of | 5-73 |
| Tilliber Corbers | 7-21 | DOUBLE LEGS | |
| DEAD LOAD | | Criteria governing use of | 6-10 |
| General discussion | 3-1 | Criteria governing use of | 0-10 |
| General discussion | 3-1 | DURATION OF LOAD | |
| DECK OVERHANG BRACKETS | | | 4-19 |
| Limitations on use | 4-34 | Adjustment factors At traffic openings | 4-19 8-3 |
| Limitations on use | 4-34 | Effect on allowable stresses | 8-3 4-2 |
| DECK SHRINKAGE | | Effect on allowable stresses | 4-2 |
| Effect on falsework | 3-18 | EXTERIOR GIRDER ROTATION | |
| Lifect off falsework | 3-10 | Prevention of | 3-13 |
| DEFLECTION | | Flevention of | 3-13 |
| Actual deflection | 3-12 | EXTERNAL BRACING | |
| Dead load deflection | 3-12 | Defined | r 0 |
| Effect on vertical clearance | 3-1 8-I | | 5-2 |
| | 3-13 | On heavy-duty shoring | 6-11 |
| Of cantilevered beam ends | | EAL OF WORK | |
| Of deck overhang | 3-12 | FALSEWORK | |
| Of sloping exterior girders | 3-13 | Definition of | 1-3 |
| Responsibility for calc. | 3-12 | Types of | 1-3 |
| Theoretical deflection | 3-1,3-11 | | |
| Upward (negative) deflection | 3-12 | FALSEWORK BRACING SYSTEM | |
| | | Definition of | 5-I |
| DEFLECTION, HORIZONTAL | | Removal of | 9-13 |
| As a design consideration | 3-15 | | |
| Effect on falsework piles (Lateral) | 7-33 | FALSEWORK CHRONOLOGICAL LOG | |
| DECICAL CALCULATIONS | | Preparation of | 2-6 |
| DESIGN CALCULATIONS | 2.4 | FALSEWORK DRAWINGS | |
| Purpose and use of | 2-4 | FALSEWORK DRAWINGS | 0.5 |
| DESIGN LOAD | | Approval of | 2-5 |
| DESIGN LOAD | 2.1 | Initial review checklist | 2-3 |
| Dead load | 3-1 | Railroad approval required | 2-5 |
| Horizontal load | 3-2 | Review sequence | 2-2 |
| Live load | 3-1 | Time for review | 2-1 |
| Minimum vertical load | 3-2 | When complete, guidelines for | 2-2 |
| On cable bracing | 4-28 | EN SEWERY EN URE MORES | |
| On construction walkways | 3-2 | FALSEWORK FAILURE MODES | |
| On diagonal bracing | 5-3,5-4,5.5 | Discussion of | 5-1 |
| On posts adjacent to traffic | 8-4 | | |
| See also Horizontal Design Load | | FALSEWORK LIGHTING | |
| See also Wind Load | | General discussion | 9-9 |
| DIAGONAL DRAGING | | FALOEWORK DADO | |
| DIAGONAL BRACING | 5 0 | FALSEWORK PADS | |
| General discussion of | 5-3 | Effective length of | 7-4,7-5,7-8 |
| Removal of | 9-13 | Inspection of foundation for | 9-2 |
| Use of cables use | 4-25,9-7 | Procedure for analysis | |
| | | Continuous pads | 7-3 |
| DIFFERENTIAL LEG LOADING | | individual pads | 7-7 |
| Limiting ratios | | | |
| For heavy-duty shoring | 6-9 | FALSEWORK PILES | |
| For pipe-frame shoring | 6-4 | General discussion | 7-23 |
| | | See also Steel Piles | |
| DIFFERENTIAL LEG SHORTENING | | See also Timber Piles | |
| As a design consideration | 6-10 | | |
| | | FALSEWORK POSTS | |
| | | See Steel Posts and Columns | |
| | | See Timber Posts | |
| | | | |

| FALSEWORK REMOVAL | | HORIZONTAL DESIGN LOAD | |
|---------------------------------------|------------|--------------------------------|-------------|
| General discussion | 9-12 | As a collapsing force | 5-5 |
| | | As an assumed load | 3-2 |
| FALSEWORK TOWERS | | Defined | 3-2 |
| See Heavy-Duty Shoring | | Purpose Of | 3-3 |
| 3 | | Where applied | |
| FIELD CHANGES | | As a collapsing force | 5-5 |
| General discussion | 9-9 | As an overturning force | 5-11 |
| | | See also Wind Load | |
| FLANGE BUCKLING | | | |
| In steel beams | 4-22 | HORIZONTAL SHEAR | |
| | | In steel beams | 4-2 1 |
| FLANGE SUPPORT SYSTEMS | | In timber beams | 4-3 |
| Design criteria | 4-24 | | . • |
| General discussion | 4-22 | HORIZONTAL STABILITY | |
| Removal of | 9-13 | See Stability | |
| | 0.0 | | |
| FORM DESIGN DATA | | IMPACT | |
| Request for | 2-1 | Duration of load factor | 4-19,8-3 |
| | | | , |
| FOUNDATION DESIGN | | INITIAL REVIEW OF F/W DRAWINGS | |
| For heavy-duty shoring | 6-10 | Information pertaining to | 2-2 |
| For pipe-frame shoring | 6-6 | g | |
| See also Falsework Pads | | INSPECTION | |
| See also Falsework Piles | | After concrete placement | 9-12 |
| | | During concrete placement | 9-11 |
| FOUNDATION MATERIAL | | Engineer's responsibility | 9-1 |
| Inspection of | 9-2 | Of cable bracing | 9-8 |
| Tests on | 9-3 | Of falsework lighting | 9-9 |
| | | Of foundation material | 9-2 |
| FRICTION | | Of manufactured products | 9-10 |
| As a design consideration | 3-17 | Of pads and sills | 9-2 |
| 7.6 a accigii conciaciancii | • | Of piles | 9-1,94 |
| HEAVY-DUTY STEEL SHORING | | Of steel shoring | 9-7 |
| Alternative design criteria | 6-8 | Of structural steel | 9-6 |
| At traffic openings | 8 4 | Of timber construction | 9-4 |
| Criteria governing use of | 6-8 | Timely insp. required | 9-1 |
| Differential leg loads | 6-9 | rimery map: required | J -1 |
| Differential leg shortening | 6-10 | INTERMEDIATE STRENGTH SHORING | |
| Double legs | 6-10 | Conditions of use | 6-6 |
| External bracing required | 6-11 | Mfgrs. statement required | 6-7 |
| | 6-11 | migis. Statement required | 0-7 |
| Foundation requirements Inspection of | 9-7 | INTERNAL STABILITY | |
| Load reduction required | 9-7 6-1 | Of timber falsework bents | 5-3 |
| | 6-8 | Of tilliber laisework belits | 5-3 |
| Modified shoring | | LAG SCREWS | |
| Safe working loads discussed | 6-I | | 4-14 |
| Safety factor | 6-8 | Criteria for design | 4-14 |
| Sidesway, effect of | 6-10 | LATERAL GURRORT OF WOOD REAMO | |
| Test load conditions | 6-1 | LATERAL SUPPORT OF WOOD BEAMS | 4.0 |
| Unequal leg settlement | 6-10 | Design guidelines | 4-6 |
| Wind loads, calc. of | 3-4 | | |
| | | LIVE LOADS | |
| HIGH-STRENGTH STEEL | | General discussion | 3-1 |
| Advantages of | 4-20 | | |
| | | LOAD TESTS On cable | |
| HORIZONTAL DEFLECTION | _ | | 4-27,4-29 |
| As a design consideration | 3-15 | On manufactured products | 4-33 |
| See also Timber Pile Bents | | On noncommercial devices | 4-33 |
| | | On soil foundations | 9-3 |

| LOCKED-IN STRESSES | | POSITIVE MEANS OF RESTRAINT | |
|---|-------------------|-------------------------------|-------------|
| Rotation of exterior girders | 3-13 | Definition of | 5-10 |
| In T-beam structures | 3-16 | | |
| LONGITUDINAL CTARILITY | | PRESTRESSING FORCES | 0.40.0.4 |
| LONGITUDINAL STABILITY | 5-9 | Effect on falsework | 3-18,8-4 |
| Provided by positive means | 5-9 | RAILROAD REQUIREMENTS | |
| Provided by positive means of resistance | 5-10 | Approval by railroad company | 2-5 |
| or resistance | 3-10 | Special design considerations | 2-5 8-6 |
| MANUFACTURED ASSEMBLIES | | Special design considerations | 0-0 |
| Catalog data required | 2-2.4-32 | REMOVAL OF FALSEWORK | |
| Definition of | 4-32 | General discussion | 9-12 |
| inspection of | 9-10 | Concrat discussion | 3 12 |
| Load test procedure | 4-33 | RESISTING CAPACITY | |
| zoda toot procedure | . 00 | Of diagonal bracing | 5-4 |
| MINIMUM VERTICAL LOAD | | or diagonal braomig | ٠. |
| As a design requirement | 3-2 | RESISTING MOMENT | |
| 3 | | Calculation of | 5-11 |
| NAILS AND SPIKES | | | |
| Criteria for joint design | 4-17 | RESPONSIBILITY | |
| | | For approval of F/W drawings | 1-4,2-I |
| OVERTURNING | | For camber calculations | 3-12 |
| As a design consideration | 5-10 | For deflection calculations | 3-12 |
| As a failure mode | 5-1 | For evaluating materials | 9-1 |
| | | For falsework construction | 1-5 |
| OVERTURNING MOMENT | | For falsework design | 1-5 |
| Calculation of | 5-11 | For inspection of falsework | 5-I |
| Effect on post loads | 5-12 | | |
| Produced by wind loads | 3-5,3-9 | REVIEW OF FALSEWORK DRAWINGS | |
| | | Chronological record of | 2-6 |
| PADS AND SILLS | | General discussion | 2-1 |
| See falsework Pads | | Incomplete drawings | 2-4 |
| | | Initial review checklist | 2-3 |
| PILES | | Procedural requirements | 2-1 |
| General Discussion | 7-23 | Responsibility for | 1-5 |
| See also Steel Pile Bents | | Time for review | 2-1 |
| See also Timber Pile Bents | | | |
| | | SAFETY FACTOR | |
| PIPE-FRAME SHORING | | For cable bracing | 4-29 |
| Allowable loads | 6-3 | For heavy-duty shoring | 6-8 |
| Analysis of | 6-4 | For manufactured products | 4-33 |
| As a manufactured product | 6-1 | OAND IAOKO | |
| Description of Inspection of | 6-2 | SAND JACKS | 0.0 |
| • | 9-7 6-1,6-3,64 | Construction and use of | 9-3 |
| Load reduction required Overturning stability | | SHEAR | |
| Safe working loads | 6-5 6-1 | Horizontal, in timber beams | 4-3 |
| Stability of | 6-5 | in steel beams | 4-3 4-21 |
| Supplemental bracing required | 6-5 | in steer beams | 4-21 |
| Test load conditions | 6-5 6-1 | SHIELDING | |
| Unequal leg load iimitation | 6-4 | Effect on wind impact area | 3-10 |
| Chicqual leg load illilitation | U- -1 | Eliect on while impact area | 3-10 |
| POINT OF FIXITY | | SOIL LOAD TESTS | |
| | .37,45.48,53 | Discussion of | 9-4 |
| . 20,00 | , , | | • • |
| PONY BENTS | | | |
| Stability of | 5-13 | | |
| | | | |

| STABILITY | | TIMBER | |
|----------------------------------|---------|-----------------------------|-------------|
| Defined | 5-1 | Construction checklist | 9-5 |
| Internal stability | 5-3 | Member size considerat ions | 4-2 |
| Longitudinal stability | 5-9 | | 7.2 |
| Of falsework systems | 5-1 | TIMBER BEAMS | |
| Of heavy-duty shoring | 6-11 | Allowable stresses | 4-1 |
| Of multiple-tower bents | 6-11 | Beam span defined | 4-2 |
| Of pipe-frame shoring | 6-5 | Bearing length required | 4-5 |
| Of steel beams | 4-23 | Bending, discussion | 4-3 |
| Of wood beams | 4-6 | Compression ⊥ grain | 4-4 |
| | | Horizontal shear in | 4-3 |
| STANDARD SPECIFICATIONS | | Lateral support of | 4-6 |
| Reference to | 1-3 | •• | |
| | | TIMBER POSTS | |
| STEEL BEAMS | | Assumed end condition | 4-6 |
| Allowable stresses | 4-20 | Design formulas for | 4-7 |
| Bending | 4-20 | Post design at F/W openings | |
| Continuous over F/W towers | 6-9 | Lateral restraint criteria | 8-3 |
| Flange buckling | 4-22 | Modified vertical load | 8-4 |
| Flange support | 4-23 | | |
| Inspection of | 5-6 | TIMBER FASTENERS | |
| Shear | 4-21 | Bolts | 4-9 |
| Web crippling | 4-22 | Drift bolts | 4-15 |
| | | Lag screws | 4-14 |
| STEEL BRACING | | Nails and spikes | 4-17 |
| Design criteria | 5-8 | Specification reference | 4-9 |
| STEEL GIRDER BRIDGES | | TIMBER PILE BENTS | |
| Deck F/W considerations | 3-20 | Adequacy of braced bents | 7-34 |
| | | Analysis of | 7-29 |
| STEEL JOIST ASSEMBLIES | | Analysis of braced bents | 7-32,34,41 |
| Limitations on use of | 4-35 | Analysis of unbraced bents | 7-32,43 |
| | | Driving tolerances | 7-26,44 |
| STEEL PILE BENTS | | Effect of pile pull | 7-30 |
| Criteria for analysis | 3-52 | Fixity. See Point of Fixity | |
| · | | General discussion | 7-23 |
| STEEL POSTS AND COLUMNS | | Longitudinal Stability | 7-41 |
| Design criteria | 4-25 | Required pile penetration | 7-24,44 |
| - | | Soil relaxation factor | 7-26 |
| STEEL SHORING | | Vectoring of Stresses | 7-50 |
| See Heavy-Duty Steel Shoring | | - | |
| See Pipe-Frame Shoring | | TINKER TOY FALSEWORK | |
| | | See Pipe-Frame Shoring | |
| STRESS ANALYSIS | | | |
| General design assumptions | 4-1 | TRAFFIC OPENINGS | |
| Policy statement | 4-1 | Bolted joints required | 8-4 |
| | | Clearance requirements | 8-1 |
| SUPPLEMENTAL BRACING | | Double caps | 8-3 |
| For heavy-duty shoring | 6-11 | Falsework lighting | 9-9 |
| For pipe-frame shoring | 6-5 | Post design load | 8-4 |
| | | Post restraint | 8-2 |
| TEMPORARY BRACING AT F/W OPENING | 3S | Railroad requirements | 8-6 |
| Design criteria | 8-4,8-6 | Temporary bracing | 8-4,8-6,9-8 |
| Purpose of | 5-8 | | |
| Removal of | 9-13 | TRIPLE LEGS | |
| When installed | 5-8 | Limitations on use of | 6-10 |
| Wind direction on | 3-4,8-6 | | |
| | | | |

| See Heavy-Duty Steel Shoring See Pipe-frame Shoring | |
|---|------|
| WEB CRIPPLING | |
| In Steel beamS | 4-22 |
| WIND IMPACT AREA | |
| Definition of | 3-4 |
| Effect of shielding | 3-10 |
| WIND LOAD | |
| Assumed wind direction | |
| On falsework | 3-8 |
| On heavy-duty shoring | 3-4 |
| General discussion | 3-3 |
| Effect of shielding | 3-10 |
| Factors affecting | 3-3 |
| On conventional falsework | 3-9 |
| On heavy duty shoring | 3-5 |
| On temporary bracing | 8-6 |
| Wind impact area defined | 3-4 |
| | |